



# CEILING - MOUNTED SPEAKERS

## 特色 (FEATURES):

### 外觀(Appearance):

防火ABS一體成形之結構，外觀採用象牙白，容易與環境裝飾搭配

One-body shape with fashion style and ivory-white color which can be fixed with the decoration easily. It adopt ABS modern design.

### 內裝(Interior):

採用安全圓形彈簧爪片，不傷手且安裝容易  
Using round soft clip, very safe and will not injure hands.



WS-801T WS-802T  
WS-100T WS-650T

## SPECIFICATIONS

TYPE	WS-100	WS-100T	WS-650	WS-650T	WS-801	WS-801T	WS-802	WS-802T
單體承受功率(Rated input)	15W	15W	35W	35W	20W	20W	35W	35W
輸入阻抗(Input impedance)	8Ω	100V Line 2W-5KΩ 4W-2.5KΩ 6W-1.67KΩ	8Ω	100V Line 2W-5K 4W-2.5K 6W-1.67K	8Ω	100V Line 2W-5K 4W-2.5K 6W-1.67K	8Ω	100V Line 2W-5K 4W-2.5K 6W-1.67K
靈敏度(Sound pressure level)	92dB	92dB	89dB	89dB	93dB	93dB	92dB	92dB
最大聲壓(MAX sound)	105dB	2W-95dB 4W-98dB 6W-100dB	104dB	2W-92dB 4W-95dB 6W-97dB	106dB	2W-96dB 4W-99dB 6W-101dB	107dB	2W-95dB 4W-98dB 6W-100dB
頻率響應(Frequency response)	80-15KHZ	80-15KHZ	60-20KHZ	60-20KHZ	80-15KHZ	80-15KHZ	60-20KHZ	60-20KHZ
喇叭單體(Speaker unit)	6.5"	6.5"	coaxial two way low 6.5" high 2"	coaxial two way low 6.5" high 2"	8"	8"	coaxial two way low 8" high 2"	coaxial two way low 8" high 2"
尺寸(約)Dimensions	φ 186X75mm	φ 186X75mm	φ 186X75mm	φ 186X75mm	φ 234X95mm	φ 234X95mm	φ 234X95mm	φ 234X95mm
重量(約)Weight	0.7kg	0.8kg	0.9kg	1.0kg	1.0kg	1.1kg	1.2kg	1.3kg
挖洞尺寸Unit part	Hole size :166mm				Hole size :207mm			

※另可選購5,10,15W匹配電壓器 (OPTIONAL ACESSORY 5.10.15W TRANSFORMER)

## PENDENT BALL SPEAKER

### 外觀(Appearance):

具ABS半球型外罩，外觀採用象牙白，容易與環境裝飾搭配


### 安裝方式(Installation):

WS-651~WS-652T 為天吊型，可懸吊固定於天花板或支架上  
WS-651R~WS-652TR 為壁掛型，具備U型牆壁固定架，可任意固定於牆壁上，並可調整聲音之指向角度

WS-651~WS-652 can hang on the ceiling or fixed on the rack shield.  
WS-651R~WS-652TR contain U shield which can be arbitrarily fixed on wall with adjustable volume and angle.



WS-651R,WS-652R  
WS-651TR,WS-652TR



WS-651,652  
WS-651T,652T

## SPECIFICATIONS

TYPE	WS-651	WS-651R	WS-651T	WS-651TR	WS-652	WS-652R	WS-652T	WS-652TR
單體承受功率(Rated input)	20W	20W	20W	20W	35W	35W	35W	35W
輸入阻抗(Linput impedance)	8Ω	8Ω	100V Line 5W-2KΩ 10W-1KΩ 15W-0.67KΩ	100V Line 5W-2KΩ 10W-1KΩ 15W-0.67KΩ	8Ω	8Ω	100V Line 5W-2KΩ 10W-1KΩ 15W-0.67KΩ	100V Line 5W-2KΩ 10W-1KΩ 15W-0.67KΩ
靈敏度(Sound pressure level)	92dB	92dB	92dB	92dB	89dB	89dB	89dB	89dB
最大聲壓(MAX sound)	105dB	105dB	5W-99dB 10W-102dB 15W-104dB	5W-99dB 10W-102dB 15W-104dB	104dB	104dB	5W-96dB 10W-99dB 15W-101dB	5W-96dB 10W-99dB 15W-101dB
頻率響應(Frequency response)	80-15KHZ	80-15KHZ	80-15KHZ	80-15KHZ	60-20KHZ	60-20KHZ	60-20KHZ	60-20KHZ
喇叭單體(Speaker unit)	6.5"	6.5"	6.5"	6.5"	coaxial two way low 6.5" high 2"	coaxial two way low 6.5" high 2"	coaxial two way low 6.5" high 2"	coaxial two way low 6.5" high 2"
尺寸(約)Dimensions	φ 186X160mm	φ 186X160mm	φ 186X160mm	φ 186X160mm	φ 186X160mm	φ 186X160mm	φ 186X160mm	φ 186X160mm
重量(約)Weight	1.4kg	1.4kg	1.6kg	1.6kg	1.5kg	1.5kg	1.7kg	1.7kg