

D79094

Triplex 4CH MPEG-4 DVR



- MPEG-4 high quality compression, 5~10 times smaller than MJPEG.
- Extremely compact volume, easy to arrange your working space.
- Excellent functions with affordable price.
- Triplex operation (recording, playback and network access) .
- Remote monitoring, playback, instant recording and dome camera control via Ethernet and / or Internet.
- Smart motion detection cell enable users to be conscious of slight motions.
- Built with ezBurn™ technology, user can simply push the COPY key for completing the video export.
- By selecting ezRecord™ function, user can select the period of days to record instead of complicated record settings.
- Support VGA main output (Optional) .
- Live display: 120pps (NTSC) / 100pps (PAL) .
- Recording Rate: Up to 120pps (NTSC)/100pps (PAL)
- 1 Channel (L & R), in & out, for audio recording
- Support up to 2 internal HDDs
- USB2.0 ports for video clip exporting, support USB ThumbDrive®
- Export DVR file which can be played via **DVRPlayer™**
- **DVRPlayer™** application software will be attached with exported devices
- Multiple built-in dome camera protocol (through RS485): BXB, Pelco D, Pelco P, AD422
- Digital Zoom 2 x 2, available in live and playback mode.
- Pre-Alarm recording.
- Support IR Remote controller (Optional) .
- Multiple language on-screen menus.
- Network software supports static IP and DHCP.
- Support RS485 remote control keyboard (optional) .

Technical Specifications

MODEL NAME		D79094		
Video	Video Standard	NTSC/PAL Switch Selectable		
	Video Operation	Triplex (Recording, Playback and Network Access)		
	Input	BNC x 4, 1.0Vp-p, 75 ohm		
	Outputs	Main Monitor	BNC x 1, 1.0Vp-p, 75 ohm	
		VGA (optional)	800 x 600, 1024 x 768, 1280 x 1024 pixels	
	Picture Refresh Rate	NTSC : 120 PPS (4CH)	PAL : 100 PPS (4CH)	
	Digital Zoom	2 X 2		
Camera Installation	Plug & Play			
Audio	Input	RCA x 2, Line-In		
	Output	RCA x 2, Line-Out		
Recording	Compression Method	MPEG-4 Advanced Simple Profile		
	Recording Mode	Schedule, Alarm, Motion Detection		
	Pre-Alarm	Yes		
	Recording Resolution & Rate	NTSC: 30 PPS@720 x 480 pixels 60 PPS@720 x 240 pixels 120 PPS@360 x240 pixels	PAL: 25 PPS@720 x 576 pixels 50 PPS@720 x 288 pixels 100 PPS@360 x 288 pixels	
	Recording Mode	Best Quality, Standard, ezRecord, Extended Record, DSL		
	Image Size	8K to 20K Byte/picture		
	Storage Mode	Linear/Circular		
Playback	Playback	Play, Stop, Pause, Rewind, Forward, Search		
	Playback Speed Adjustment	Yes, 1X, 2X...32X		
	Retrieve	Date/Time, Event		
Storage	Built-in HDD	Up to 2 built-in HDDs		
Export	USB Protocol	USB 2.0		
	USB ThumbDrive	Supported		
Alarm	Alarm Input	X4, D-Sub 15 pin		
	Alarm Relay Output	X1, D-Sub 15 pin		
	Alarm Detection	N.C./N.O., Programmable		
	Motion Detection	16 X 12		
	Video Loss Detection	Programmable		
	Auditory Alert	Built-in Buzzer		
Communication	Communication Protocol	RS-485 DSCP		
	Remote Control Software	DVRRemote™ Lite		
	Network Connectivity	Ethernet RJ-45 connector, 10/100Mbps, supports DHCP		
	LAN Remote Control	IE Browser, Windows AP		
	Dome Control	IE Browser, Windows AP, Front Panel		
	Remote Operation	Monitor, Playback, System Setup, Dome Camera Control		
On-Screen Display	Search	Based on Time or Event		
	Play/Pause/REW/FF	Control Playback Direction & Speed		
	Password Control	2 level, Administrator/User		
General	Unit Dimension(WxHxD)	220(W) x 340(D) x 50(H)mm		
	Unit Weight	3.2kg (including 2 internal HDDs)		
	Package Dimension(WxHxD)	450mm x 400mm x 150mm		
	Package Weight	4.3kg		
	Operation Temperature	0°C - 40°C(32°F - 104°F)		
	Relative Humidity	30% - 90% Non-condensing		
	Power Consumption & Input/output	External Adaptor, AC 100~240V/ in, DC12V (5A) / out, 50-60Hz, Max 60W		

PRODUCT SELECTION 79094-□□□X₁X₂

□ - Color
 B:Black
 S:Silver

□□ - HDD
 00: None
 16: 160GB
 20: 200GB
 50: 500GB

X₁ – Devices Option
 O:None
 V:VGA
 R:Remote Controller

X₂ – Video System
 P:PAL
 N:NTSC

KEY DEFINITION

● IR ● POWER ● REC ● ALARM ● NETWORK

1	2	DOME	MODE	SEQ	MENU
3	4	COPY	PLAY/ STOP	FREEZE	SEARCH

ESC/ LOCK	^	ENTER
<	v	>

Product specifications and availability subject to change without no
 Certain product names mentioned herein may be trade names and/or registered trademarks of their companies.



6F.-1, No.288-5, Xinya Rd., Qianzhen Dist., Kaohsiung City 806, Taiwan (R.O.C.)

TEL : +886 (7) 970-3838 FAX : +886 (7) 970-3883

<http://www.bxb.tw> E-Mail: bxb@bxb.tw