

PA 5120PQ

Pre-Mixer Amplifier

(120W)



This PA-5120PQ series, the latest and easiest conference system with superb performance and elegant design, can be used for various conferencing.

PA-5120PQ (120W) or PA-5120P2 (240W) can provide power for up to 50 conference units. It can also connect with power extension supply for more units based on actual requirement.

PA-5120 series provides the unique features of pre-mixer, amplifier, sound effect processor, making it high reliability.

All products and accessories are gone through strict testing from BXB's certified ISO 9001 factory and many international certifications, such as RoHS, UKAS, CE, LVD, EMC BSMI and etc. The excellent performance, high reliability and reasonable price make it become the useful devices for your conference system.

TECHNICAL SPECIFICATIONS

Rated Output	120W (RMS), 180(MAX)
Speaker output	100V (167Ω) / 70V (82Ω) / 4~16Ω
Frequency response	20HZ ~ 20KHZ
Total Harmonic Distortion	<1% (1kHz)
S/N ratio	MIC > 60dB · AUX >70dB
BASS	100Hz ±10dB
Treble	10KHz ±10dB
AUX INPUT	4 sets with 4 individual volume control
Sensitivity and impedance	-22dBV 100mV 10KΩ unbalanced, RCA jack
MIC input	4 sets with individual volume control
MIC input Sensitivity and impedance	-65dBV 0.5mV 600Ω unbalanced, PHONE jack
attenuation	0~30dB
recovery time	3 seconds
Control Zone Switch	Five (5) + All CALL
REC output	0dB/100mV/10kΩ unbalanced, RCA jack
'Priority' Muting Jack	MIC 1 & 2
AUX OUTPUT	10kΩ~22kΩ unbalanced, RCA jack
Volume Indicators	5 LEDs
Power	AC110~120V/ 220~230V (50/ 60HZ)
Height x Width x Depth	100 x 430 x 230 (mm)
Weight	10 KG

*The appearance and specifications of all item are subject to change without notice